



Approval	
Capability	
Standard	
Rated Voltage	
Rated Current	
Wire size	
T/W/End plate	
Height(mm)(NS35:7.5/NS35:15/NS32)	
Rated surge voltage/Contamination Class	
Stripping length	
Screw thread/Tightening torque	
Internal cylindrical gage	
Insulating Material/Inflammability class	

c us	
UL	IEC
600V	800V
85A	76A
12-4AWG	0.2-16mm ²
	12.2/42.5/1.5mm
	54/61.5/59mm
	8KV/3
	11mm
	M4/1.2N.m/10.5Lb-in
	B7
	PAV-0

- | Specification | Model | Pieces |
|------------------------------------|-------------|--------|
| (1) Terminal block | PC 16 | 50 |
| (2) End cover | D-PC 16 | 150 |
| (3) Fixed bridge | | |
| 2-P | | |
| 3-P | | |
| 5-P | | |
| 10-P | | |
| (4) Step bracket | FBI 10-12 | 100 |
| (5) Insertion bridge | | |
| 2-P | | |
| 3-P | | |
| 10-P | | |
| (6) Isolator bridge bar, 10P | EB 10-12 | 50 |
| (7) Bridge bar isolator | | |
| (8) Switching bridge | | |
| (9) Separating plate | TS-K | 50 |
| (10) Separating plate, width 1.5mm | ATP-PC | 50 |
| (11) Test plug socket | DSB 4/7/6 | 100 |
| (12) Test plug socket, insulated | DSBJ 4/15/6 | |
| (13) Zack strip | ZB10 | 200 |

HOW TO ORDER :

 - **P** - 1 - X X X

Series No. **No. of pole** **Color**

1 Gray	4 Green	7 Transp-arent
2 Blue	5 Orange	8 Yellow
3 Black	6 Red	9 white

Customer Request