


| Approval  |          |                      |        |
|---|----------|----------------------|--------|
| Capability  |          |                      |        |
| Standard  | UL       | IEC                  |        |
| Rated Voltage   | -        | -                    |        |
| Rated Current   | -        | -                    |        |
| Wire size   | 6-1/0AWG | 25-50mm <sup>2</sup> |        |
| T/W/End plate   |          | 20/70.5/-mm          |        |
| Height(mm)(NS35:7.5/NS35:15/NS32)   |          | -/83.5/81.5mm        |        |
| Rated surge voltage/Contamination Class   |          | 8KV/3                |        |
| Stripping length  |          | 24mm                 |        |
| Terminal screw: thread/torque   |          | M6/2.5N.m/22Lb-in    |        |
| Mounting screw: thread/torque   |          | M6/2.5N.m/22Lb-in    |        |
| Internal cylindrical gage   |          | B10                  |        |
| Insulating Material/Inflammability class  |          | PAV-0                |        |
| Specification   |          | Model                | Pieces |
| (1)Ground terminal block  |          | PC 50-PE             | 10     |
| (2)Insertion profile  |          | PC 50EP              | 10     |
| (3)Zack strip  |          | ZB 10                |        |

### HOW TO ORDER :

  -     **P** - 1   - X X X  
Customer Request

|   |       |   |        |   |                  |
|---|-------|---|--------|---|------------------|
| 1 | Gray  | 4 | Green  | 7 | Transp-<br>arent |
| 2 | Blue  | 5 | Orange | 8 | Yellow           |
| 3 | Black | 6 | Red    | 9 | white            |

|  |  |
|--|--|
| <br>mm<br>(INCH)          |  <b>China · Kang Wei electronics co., LTD</b> |
| <br>THIROANGLE PROJECTION | <b>NAME</b><br><span style="font-size: 1.5em; font-weight: bold;">UK50JD</span>  |