



Approval

Electrical
Standard
Rated voltage
Rated current
Wire size
T/W/End plate
Height(NS35:7.5/NS35:15/NS32)
Rated surge voltage/Contamination class
Stripping length
Screw thread/Tightening torque
Internal cylindrical gage
Insulating material/Inflammability class

CE

UL	IEC
300V	400V
40A	41A
26-10AWG	0.5-6.0mm ²
8.2/72/2mm	
51.5/59/56mm	
6KV/3	
13mm	
M4/1.2N.m/10.5Lb-in/ M3/0.5N.m/4.5Lb-in	
A5	
PAV-0	

Specification

- (1) Terminal block
- (2) Cover
- (3) Fixed bridge
 - 2P
 - 3P
 - 5P
 - 10P
- (4) Switching bridge
- (5) Switching bridge
- (6) Switching bridge
- (7) Switching bridge
- (8) Switching Lock
- (9) Separating plate, thick 0.8mm
- (10) Partition plate
- (11) Zack strip

Model Pieces

Model	Pieces
PCTK 6	50
D-PCTK 6	100
FB 2-RTK/S	50
FB 3-RTK/S	30
FB 5-RTK/S	10
FB 10-RTK/S	10
USB 2-RTK/S	10
ASB 2-RTK/S	10
SB 2-RTK/S	10
SB 4-RTK/S	10
S	100
TS-RTK	50
ATS-RTK	100
ZB8	300

HOW TO ORDER :

 - **P** - 1 - X X X
Customer Request

Series No.
No. of pole
Color

1 Gray	4 Green	7 Transp-arent
2 Blue	5 Orange	8 Yellow
3 Black	6 Red	9 white