


DK4QV


Approval
Electrical
Standard
Voltage
Current
Wire size
T/W/End plate
Height(NS35:7.5/NS35:15/NS32)
Rated surge voltage/Contamination class
Stripping length
Screw thread/Tightening torque
Insulating material/Inflammability class

C  US		CE
UL		IEC
300V		500V
20A		32A
22-12AWG		0.5-4.0mm <sup>2</sup>
		6/54/1.5mm
		60.5/68/60mm
		6KV/3
		8mm
		M3/0.5N.m/12.5Lb-in
		PA/V-0

### HOW TO ORDER :

<input type="text"/>	-	<input type="text"/> <input type="text"/> P	-	<input type="text"/> 1 <input type="text"/>	-	<table><tr><td>X</td><td>X</td><td>X</td></tr><tr><td colspan="3">Customer Request</td></tr></table>	X	X	X	Customer Request						
X	X	X														
Customer Request																
Series No.		No. of pole		Color												
				<table><tr><td>1 Gray</td><td>4 Green</td><td>7 Transp-arent</td></tr><tr><td>2 Blue</td><td>5 Orange</td><td>8 Yellow</td></tr><tr><td>3 Black</td><td>6 Red</td><td>9 white</td></tr></table>	1 Gray	4 Green	7 Transp-arent	2 Blue	5 Orange	8 Yellow	3 Black	6 Red	9 white			
1 Gray	4 Green	7 Transp-arent														
2 Blue	5 Orange	8 Yellow														
3 Black	6 Red	9 white														

mm  
(INCH)



THIROANGLE PROJECTION



China · Kang Wei electronics co., LTD

NAME

DK4QV