



|                      |   |   |
|----------------------|---|---|
| <b>APPROVAL</b>      |  |  |
| <b>Electrical</b>    |   |   |
| Standard             | <b>UL</b>   | <b>IEC</b>  |
| Rated voltage        | 300V  | 250V  |
| Rated current        | 10A   | 18A   |
| Wire range           | 24-12AWG  | 2.5mm <sup>2</sup>  |
| Withstanding voltage | AC2000V/1Min  |   |

|                     |                              |
|---------------------|------------------------------|
| <b>Menchanical</b>  |                              |
| Torque              | 0.4Nm(3.5Lb-In)              |
| Ambient temperature | -40°C~+105 °C                |
| Strip length        | 7mm                          |
| <b>Dimensions</b>   |                              |
| pitch               | 5.0mm(.197" ) 5.08mm(.200" ) |
| Poles               | 2*(2P,3P-24P)                |

|                 |                                       |
|-----------------|---------------------------------------|
| <b>Material</b> |                                       |
| Housing         | PA66,UL94V-0                          |
| Screws          | M2.5,Steel, Cr <sup>3+</sup> Znplated |
| Pin header      | Brass,Tin-plated                      |
| Cage            | Brass,Ni-plated                       |

**HOW TO ORDER :**

